



GENERAL SPECIFICATIONS



Characteristics	Mirage Classic			
	Sweet Memories Series - Aged Maple			
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel [on 4 sides] • An exclusive variable staining process 			
Thickness	3/4" [19 mm]			
Length	• Random lengths [from 10" [250 mm] to 76" [1,930 mm]]			
Width	3-1/4" [83 mm], 4-1/4" [108 mm]			
Species	1 species: Maple			
Grade	• Sweet Memories - Aged Maple [These floors present pronounced color variations, repaired and sound knots, surface holes, hairline cracks, mineral streaks, and other character marks].			
Color choice [refer to 2012 Mirage Collections]	7 colors: Nougat, Praline, Gingerbread, Brownie, Black Jelly Bean, Toffee, Truffle			
Finish	• Nanolinx™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.			
	• Cashmere®*			
	Appearance:	Superior	Durability:	Superior
	Gloss losing resistance:	Superior	Stain resistance:	Superior
	Easy to maintain:	Superior	Easy to repair:	Superior
	UV Protection: All products		Formaldehyde: Free	
	Water and solvent: No trace			
	Static Friction Coefficient [ASTM-D-2047]: Slippery resistance of 0.5 to 0.55			
Applicable standards	Surface Burning [ASTM-E-84]:		Surface Burning [ULC-S-102-2]:	
	• FSI [Flame Spread Index] 100 to 150 Classe C [depends on wood species]		• FSC [Flame Spread Classification] 100 to 150 [depends on wood species]	
	• SD [Smoke Development] 75 to 400 [depends on wood species]		• SD [Smoke Development] 200 to 300 [depends on wood species]	
	Critical radiant flux [ASTM-E-648-94a]: 0.25 to 0.40 watt/cm ² [depends on wood species]		R value: R 0.6 to 0.8 [depends on wood species]	
	Formaldehyde emission [ASTM-E-1333-02]: • Less than 0.01 ppm		Total VOC [ASTM-D-6670-01]: • 0.003 ppm [depends on wood species]	
Installation	Nailed or stapled down [above and on grade]			
Subfloor	Wood			
Maintenance	Quick and easy with Mirage Clean maintenance kit			
Use	Residential or light commercial			
Accessory	Stair nosing, Round reducer, Carpet reducer, Threshold, "T" molding, Quarter round			
Warranty	• Structural lifetime limited warranty		• 3-year finish warranty for light commercial applications	
	• 25-year finish warranty for residential applications			
Packaging	3-1/4"		4-1/4"	
Content of a box	• 20 ft ² [1,858 m ²]		• 18 ft ² [1,672 m ²]	
Size of a box	• 82" L x 10-1/2" W x 3-1/4" H		• 86" L x 9" W x 3-1/4" H	
Weight of a box	• 49 to 75 lbs		• 49 to 51 lbs	
Content of a pallet	• 48 boxes = 960 ft ²		• 50 boxes = 900 ft ²	
	[4 boxes/W x 12 boxes/H]		[5 boxes/W x 10 boxes/H]	
Size of a pallet	• 82" L x 42" W x 43" H		• 86" L x 46" W x 36" H	
Relative species hardness				
NWFA Janka Test Hardness test [ASTM-D-143]	• Maple	1,450 lbs - 12% harder		
Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds				

* Cashmere is a registered trademark used under license.



GENERAL SPECIFICATIONS



Characteristics	Mirage Engineered			
	2-9/16" [65 mm]		3-5/16" [84 mm]	
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel [on 4 sides] 			
Thickness	• 3/8" [10 mm] [Sawn hardwood layer 5/32" [4 mm], 5-ply plywood base 7/32" [6 mm]]			
Width	2-9/16" [65 mm]		3-5/16" [84 mm]	
Species	8 species: Maple, Yellow Birch, Red Oak, American Cherry, American Walnut, Brazilian Cherry [Jatoba], Santos Mahogany [Cabreuva], Sapele		9 species: Maple, Yellow Birch, Canadian Breza, Red Oak, American Cherry, American Walnut, Brazilian Cherry [Jatoba], Santos Mahogany [Cabreuva], African Mahogany	
Grade	<ul style="list-style-type: none"> Select & Better [Selection of more uniform wood grain with slight variations in natural shading] Exclusive [As found in nature. A complete species color and character range] 			
Color choice [refer to 2012 Mirage Collections]	23 colors: Natural, Sonora, Golden, Sierra, Savanna, Colorado, Rich Oak, Montana, Canyon, Cognac, Nevada, Auburn, Henna, Onyx, Bali Cocco, Alaska, Greystone, Charcoal, Graphite, Java, Umbria, Vienna, Sambuca			
Finish	<ul style="list-style-type: none"> Nanolinx™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Nanolinx™ Premium [commercial]: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Semi-gloss or Cashmere®* 			
	Appearance:	Superior	Durability:	Superior
	Gloss losing resistance:	Superior	Stain resistance:	Superior
	Easy to maintain:	Superior	Easy to repair:	Superior
	UV Protection: All products		Formaldehyde: Free	
	Water and solvent: No trace			
	Static Friction Coefficient [ASTM-D-2047]: Slippery resistance of 0.5 to 0.55			
Applicable standards	Surface Burning [ASTM-E-84]: <ul style="list-style-type: none"> FSI [Flame Spread Index] 100 to 150 Classe C [depends on wood species] SD [Smoke Development] 75 to 400 [depends on wood species] 		Surface Burning [ULC-S-102-2]: <ul style="list-style-type: none"> FSC [Flame Spread Classification] 100 to 150 [depends on wood species] SD [Smoke Development] 200 to 300 [depends on wood species] 	
	Critical radiant flux [ASTM-E-648-94a]: 0.25 to 0.40 watt/cm ² [depends on wood species]		R value: R 0.3 to 0.4 [depends on wood species]	
	Formaldehyde emission [ASTM-E-1333-02]: Less than 0.01 ppm		Total VOC [ASTM-D-6670-01]: Less than 0.011 ppm [depends on wood species]	
Installation	Stapled or glued down [above, on or below grade]			
Subfloor	Wood, concrete or radiant heat system [with the exception of Brazilian Cherry [Jatoba]]			
Maintenance	Quick and easy with Mirage Clean maintenance kit			
Use	Residential, light commercial or commercial [Nanolinx™ Premium]			
Accessory	Stair nosing, Round reducer, Threshold, "T" molding, Quarter round			
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty 25-year finish warranty for residential applications 		<ul style="list-style-type: none"> 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx™ Premium 	
Board length				
6 assorted lengths in each box	± 13-3/4 inches [350 mm]	± 17-7/8 inches [455 mm]	± 13-3/4 inches [350 mm]	± 16-5/8 inches [420 mm]
	± 23-1/2 inches [595 mm]	± 29 inches [736 mm]	± 22-7/8 inches [576 mm]	± 28-7/8 inches [732 mm]
	± 33-1/8 inches [841 mm]	± 46-7/8 inches [1,191 mm]	± 31-7/8 inches [802 mm]	± 45-3/8 inches [1,152 mm]
Packaging				
Content of a box	• 20 ft ² [1,858 m ²]		• 25 ft ² [2,322 m ²]	
Size of a box	• 48" L x 8-1/4" W x 3-1/4" H		• 46-1/2" L x 10-1/4" W x 3-1/4" H	
Weight of a box	• 27 to 34 lbs		• 34 to 41 lbs	
Content of a pallet	• 50 boxes = 1,000 ft ² [5 boxes/W x 10 boxes/H]		• 40 boxes = 1,000 ft ² [4 boxes/W x 10 boxes/H]	
Size of a pallet	• 48" L x 42-1/4" W x 37" H		• 46-1/2" L x 42" W x 37" H	
Relative species hardness				
NWFA Janka Test	• American Cherry	950 lbs - 26% softer	• Maple	1,450 lbs - 12% harder
Hardness test [ASTM-D-143]	• American Walnut	1,010 lbs - 22% softer	• Sapele	1,500 lbs - 16% harder
	• Canadian Breza	1,200 lbs - 7% softer	• African Mahogany	1,500 lbs - 16% harder
	• Yellow Birch	1,260 lbs - 2% softer	• Santos Mahogany [Cabreuva]	2,200 lbs - 71% harder
	• Red Oak	1,290 lbs - average hardness	• Brazilian Cherry [Jatoba]	2,350 lbs - 82% harder
	Red Oak 1290 lbs* - 100%			
*lbs = Applied force in pounds				

* Cashmere is a registered trademark used under license.



GENERAL SPECIFICATIONS



Characteristics	Mirage Engineered	
	5" [127 mm]	6-1/2" [165 mm]
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel [on 4 sides] 	
Thickness	<ul style="list-style-type: none"> 1/2" [13 mm] [Sawn hardwood layer 5/32" [4 mm], 7-ply plywood base 11/32" [9 mm]] 	
Width	5" [127 mm]	6-1/2" [165 mm]
Species	7 species: Maple, Red Oak, American Walnut, Hickory, African Mahogany, Brazilian Cherry [Jatoba], Sapele	3 species: Maple, Red Oak, Hickory
Grade	<ul style="list-style-type: none"> Exclusive [As found in nature. A complete species color and character range] Knotty Walnut [These floors are appreciated for their pronounced color variations. They feature mineral streaks, sound and repaired knots, surface holes, pith, hairline surface cracks, and natural imperfections] Old Hickory [These floors present pronounced color variations, repaired and sound knots, surface holes, hairline cracks, mineral streaks, and other character marks.] 	
Color choice [refer to 2012 Mirage Collections]	19 colors: Natural, Sonora, Golden, Sierra, Savanna, Colorado, Montana, Nevada, Auburn, Old Hickory, Brass, Terracotta, Henna, Bronze, Onyx, Greystone, Charcoal, Graphite, Umbria, Vienna	
Finish	<ul style="list-style-type: none"> Nanolinx™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Nanolinx™ Premium [commercial]: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Semi-gloss or Cashmere®* 	
	Appearance: Superior	Durability: Superior
	Gloss losing resistance: Superior	Stain resistance: Superior
	Easy to maintain: Superior	Easy to repair: Superior
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	
	Static Friction Coefficient [ASTM-D-2047]: Slippery resistance of 0.5 to 0.55	
Applicable standards	Surface Burning [ASTM-E-84]: <ul style="list-style-type: none"> FSI [Flame Spread Index] 100 to 150 Classe C [depends on wood species] SD [Smoke Development] less than 400 [depends on wood species] 	Surface Burning [ULC-S-102-2]: <ul style="list-style-type: none"> FSC [Flame Spread Classification] 80 [depends on wood species] SD [Smoke Development] max 350 [depends on wood species]
	Critical radiant flux [ASTM-E-648-94a]: 0.41 watt/cm² [depends on wood species]	R value: R 0.44 to 0.51 [depends on wood species]
	Formaldehyde emission [ASTM-E-1333-02]: Less than 0.01 ppm	Total VOC [ASTM-D-6670-01]: 0.011 ppm [depends on wood species]
Installation	Stapled or glued down [above, on or below grade]	
Subfloor	Wood, concrete or radiant heat system [with the exception of Brazilian Cherry [Jatoba]]	
Maintenance	Quick and easy with Mirage Clean maintenance kit	
Use	Residential, light commercial or commercial [Nanolinx™ Premium]	
Accessory	Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty 25-year finish warranty for residential applications 	<ul style="list-style-type: none"> 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx™ Premium
Board length		
6 assorted lengths in each box	<ul style="list-style-type: none"> ± 19 inches [482 mm] ± 25-1/2 inches [648 mm] ± 30 inches [762 mm] ± 34-1/2 inches [876 mm] ± 41 inches [1,042 mm] ± 60 inches [1,524 mm] 	<ul style="list-style-type: none"> ± 19-11/16 inches [500 mm] ± 25-1/2 inches [648 mm] ± 34-5/8 inches [879 mm] ± 43-11/16 inches [1,100 mm] ± 49-1/2 inches [1,258 mm] ± 69-3/16 inches [1,758 mm]
Packaging		
Content of a box	25 ft² [2,322 m²]	25 ft² [2,322 m²]
Size of a box	61" L x 10-1/4" W x 3-1/4" H	70" L x 7" W x 3-1/4" H
Weight of a box	46 to 51 lbs	46 to 51 lbs
Content of a pallet	40 boxes = 1,000 ft² [4 boxes/W x 10 boxes/H]	42 boxes = 1,050 ft² [6 boxes/W x 7 boxes/H]
Size of a pallet	61" L x 42" W x 37" H	70" L x 42" W x 33" H
Relative species hardness		
NWFA Janka Test	American Walnut	1,010 lbs - 22% softer
Hardness test [ASTM-D-143] Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds	Red Oak	1,290 lbs - average hardness
	Maple	1,450 lbs - 12% harder
	Sapele	1,500 lbs - 16% harder
	African Mahogany	1,500 lbs - 16% harder
	Hickory	1,820 lbs - 41% harder
	Brazilian Cherry [Jatoba]	2,350 lbs - 82% harder

* Cashmere is a registered trademark used under license.



GENERAL SPECIFICATIONS



Characteristics	Mirage Engineered	
	Sweet Memories Series - Aged Maple	
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel [on 4 sides] An exclusive variable staining process 	
Thickness	• 1/2" [13 mm] [Sawn hardwood layer 5/32" [4 mm], 7-ply plywood base 11/32" [9 mm]]	
Width	5" [127 mm]	6-1/2" [165 mm]
Species	1 species: Maple	
Grade	• Sweet Memories - Aged Maple [These floors present pronounced color variations, repaired and sound knots, surface holes, hairline cracks, mineral streaks, and other character marks].	
Color choice <small>[refer to 2012 Mirage Collections]</small>	7 colors: Toffee, Truffle, Nougat, Praline, Gingerbread, Brownie, Black Jelly Bean	
Finish	<ul style="list-style-type: none"> Nanolinx™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Cashmere®* 	
	Appearance: Superior	Durability: Superior
	Gloss losing resistance: Superior	Stain resistance: Superior
	Easy to maintain: Superior	Easy to repair: Superior
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	
	Static Friction Coefficient [ASTM-D-4518-91]: Slippery resistance of 0.5 to 0.55	
Applicable standards	Surface Burning [ASTM-E-84]: <ul style="list-style-type: none"> FSI [Flame Spread Index] 100 to 150 Classe C [depends on wood species] SD [Smoke Development] less than 400 [depends on wood species] 	Surface Burning [ULC-S-102-2]: <ul style="list-style-type: none"> FSC [Flame Spread Classification] 80 [depends on wood species] SD [Smoke Development] max 350 [depends on wood species]
	Critical radiant flux [ASTM-E-648-94a]: 0.41 watt/cm ² [depends on wood species]	R value: R 0.44 to 0.51 [depends on wood species]
	Formaldehyde emission [ASTM-E-1333-02]: Less than 0.01 ppm	Total VOC [ASTM-D-6670-01]: 0.011 ppm [depends on wood species]
Installation	Stapled or glued down [above, on or below grade]	
Subfloor	Wood, concrete or radiant heat system	
Maintenance	Quick and easy with Mirage Clean maintenance kit	
Use	Residential or light commercial	
Accessory	Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty 25-year finish warranty for residential applications 	• 3-year finish warranty for light commercial applications
Board length		
6 assorted lengths in each box	± 19 inches [482 mm] ± 25-1/2 inches [648 mm] ± 30 inches [762 mm] ± 34-1/2 inches [876 mm] ± 41 inches [1,042 mm] ± 60 inches [1,524 mm]	± 19-11/16 inches [500 mm] ± 25-1/2 inches [648 mm] ± 34-5/8 inches [879 mm] ± 43-11/16 inches [1,110 mm] ± 49-1/2 inches [1,258 mm] ± 69-3/16 inches [1,758 mm]
Packaging		
Content of a box	• 25 ft ² [2,322 m ²]	• 25 ft ² [2,322 m ²]
Size of a box	• 61" L x 10-1/4" W x 3-1/4" H	• 70" L x 7" W x 4-1/4" H
Weight of a box	• 46 to 51 lbs	• 46 to 51 lbs
Content of a pallet	• 40 boxes = 1,000 ft ² [4 boxes/W x 10 boxes/H]	• 42 boxes = 1,050 ft ² [6 boxes/W x 7 boxes/H]
Size of a pallet	• 61" L x 42" W x 37" H	• 70" L x 42" W x 33" H
Relative species hardness		
NWFA Janka Test Hardness test [ASTM-D-143]	• Maple	1,450 lbs - 12% harder
Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Engineered	
	Sweet Memories Series - Handcrafted Oak	
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel [on 4 sides] Weathered look 	
Thickness	• 1/2" [13 mm] [Sawn hardwood layer 5/32" [4 mm], 7-ply plywood base 11/32" [9 mm]]	
Width	5" [127 mm]	6-1/2" [165 mm]
Species	1 species: Red Oak	
Grade	<ul style="list-style-type: none"> Sweet Memories - Handcrafted Oak [These floors present pronounced color variations, open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.] 	
Color choice <small>[refer to 2012 Mirage Collections]</small>	3 colors: Carousel, Château, Teddy Bear	
Finish	<ul style="list-style-type: none"> Nanolinx™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Cashmere®* 	
	Appearance:	Superior
	Gloss losing resistance:	Superior
	Easy to maintain:	Superior
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	Static Friction Coefficient [ASTM-D-4518-91]: Slippery resistance of 0.5 to 0.55
Applicable standards	Surface Burning [ASTM-E-84]: <ul style="list-style-type: none"> FSI [Flame Spread Index] 100 to 150 Classe C [depends on wood species] SD [Smoke Development] less than 400 [depends on wood species] 	Surface Burning [ULC-S-102-2]: <ul style="list-style-type: none"> FSC [Flame Spread Classification] 80 [depends on wood species] SD [Smoke Development] max 350 [depends on wood species]
	Critical radiant flux [ASTM-E-648-94a]: 0.41 watt/cm ² [depends on wood species]	R value: R 0.44 to 0.51 [depends on wood species]
	Formaldehyde emission [ASTM-E-1333-02]: Less than 0.01 ppm	Total VOC [ASTM-D-6670-01]: 0.011 ppm [depends on wood species]
Installation	Stapled or glued down [above, on or below grade]	
Subfloor	Wood, concrete or radiant heat system	
Maintenance	Quick and easy with Mirage Clean maintenance kit	
Use	Residential or light commercial	
Accessory	Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty 25-year finish warranty for residential applications 	<ul style="list-style-type: none"> 3-year finish warranty for light commercial applications
Board length		
6 assorted lengths in each box	± 19 inches [482 mm] ± 25-1/2 inches [648 mm] ± 30 inches [762 mm] ± 34-1/2 inches [876 mm] ± 41 inches [1,042 mm] ± 60 inches [1,524 mm]	± 19-11/16 inches [500 mm] ± 25-1/2 inches [648 mm] ± 34-5/8 inches [879 mm] ± 43-11/16 inches [1,110 mm] ± 49-1/2 inches [1,258 mm] ± 69-3/16 inches [1,758 mm]
Packaging		
Content of a box	• 25 ft ² [2.322 m ²]	• 25 ft ² [2.322 m ²]
Size of a box	• 61" L x 10-1/4" W x 3-1/4" H	• 70" L x 7" W x 4-1/4" H
Weight of a box	• 46 to 51 lbs	• 46 to 51 lbs
Content of a pallet	• 40 boxes = 1,000 ft ² [4 boxes/W x 10 boxes/H]	• 42 boxes = 1,050 ft ² [6 boxes/W x 7 boxes/H]
Size of a pallet	• 61" L x 42" W x 37" H	• 70" L x 42" W x 33" H
Relative species hardness		
NWFA Janka Test Hardness test [ASTM-D-143]	• Red Oak 1,290 lbs - average hardness	
Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.



GENERAL SPECIFICATIONS



Characteristics	Mirage Engineered			
	Herringbone Series			
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongue and groove edges, and grooves at both ends Micro-V bevel [on 4 sides] 			
Thickness	• 3/8" [10 mm] [Sawn hardwood layer 5/32" [4 mm], 5-ply plywood base 7/32" [6 mm]]			
Length	• 13-3/4" [350 mm] and 17-7/8" [455 mm]			
Width	2-9/16" [65 mm]			
Species	5 species: Maple, Red Oak, Brazilian Cherry [Jatoba], American Cherry, American Walnut			
Grade	• Exclusive [As found in nature. A complete species color and character range]			
Color choice [refer to 2012 Mirage Collections]	Many colors available on special order			
Finish	<ul style="list-style-type: none"> Nanolinx™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Nanolinx™ Premium [commercial]: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Semi-gloss or Cashmere®* 			
	Appearance:	Superior	Durability:	Superior
	Gloss losing resistance:	Superior	Stain resistance:	Superior
	Easy to maintain:	Superior	Easy to repair:	Superior
	UV Protection:	All products	Formaldehyde:	Free
	Water and solvent: No trace			
	Static Friction Coefficient [ASTM-D-2047]: Slippery resistance of 0.5 to 0.55			
Applicable standards	Surface Burning [ASTM-E-84]:	Surface Burning [ULC-S-102-2]:		
	<ul style="list-style-type: none"> FSI [Flame Spread Index] 100 to 150 Classe C [depends on wood species] SD [Smoke Development] 75 to 400 [depends on wood species] 	<ul style="list-style-type: none"> FSC [Flame Spread Classification] 100 to 150 [depends on wood species] SD [Smoke Development] 200 to 300 [depends on wood species] 		
	Critical radiant flux [ASTM-E-648-94a]:	R value: R 0.3 to 0.4 [depends on wood species]		
	0.25 to 0.40 watt/cm² [depends on wood species]			
Formaldehyde emission [ASTM-E-1333-02]:	Total VOC [ASTM-D-6670-01]:			
Less than 0.01 ppm	Less than 0.011 ppm [depends on wood species]			
Installation	Glued down [above, on or below grade]			
Subfloor	Wood, concrete or radiant heat system [with the exception of Brazilian Cherry [Jatoba]]			
Maintenance	Quick and easy with Mirage Clean maintenance kit			
Use	Residential, light commercial or commercial [Nanolinx™ Premium]			
Accessory	Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round			
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty 25-year finish warranty for residential applications 	<ul style="list-style-type: none"> 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx™ Premium 		
Patterns	Length: 13-3/4" [350 mm]	Length: 17-7/8" [455 mm]		
	<ul style="list-style-type: none"> Herringbone Double Herringbone English pattern [bricks] 	<ul style="list-style-type: none"> Herringbone Double Herringbone English pattern [bricks] Basket Cube 		
Packaging	Length: 13-3/4" [350 mm]	Length: 17-7/8" [455 mm]		
Content of a box	• 17.63 ft² [1.638 m²]	• 15.28 ft² [1.420 m²]		
Size of a box	• 42-1/2" L x 8-1/4" W x 3-1/4" H	• 37-1/4" L x 8-1/4" W x 3-1/4" H		
Weight of a box	• 25 to 29 lbs	• 22 to 27 lbs		
Content of a pallet	• 40 boxes = 705.2 ft² [5 boxes/W x 8 boxes/H]	• 40 boxes = 611.2 ft² [5 boxes/W x 8 boxes/H]		
Size of a pallet	• 42-1/2" L x 42" W x 30" H	• 37-1/4" L x 42" W x 30" H		
Relative species hardness				
NWFA Janka Test	• American Cherry	950 lbs - 26% softer		
Hardness test [ASTM-D-143]	• American Walnut	1,010 lbs - 22% softer		
	• Red Oak	1,290 lbs - average hardness		
Red Oak 1290 lbs* - 100%	• Maple	1,450 lbs - 12% harder		
*lbs = Applied force in pounds	• Brazilian Cherry [Jatoba]	2,350 lbs - 82% harder		

* Cashmere is a registered trademark used under license.

